

This guide describes how to install the Windows-compliant printer driver, fax driver, and scan driver included in this CD.

Version 1.0

[Contents]

I. Before Getting Started

I-I. Network Connection

I-II. Local Connection

II. Installing Drivers

II-I. Network Connection

II-II. Local Connection

I. Before Getting Started

Before installing drivers, check the following.

- Installing drivers requires administrator privileges of your computer.
- If the window related to [User Account Control] appears, click [Allow] or [Continue].

I-I. Network Connection

Network connection is to connect the printer/MFP to the network such as the intra-LAN.

Check with the network administrator to make sure that the printer/MFP is connected to the network normally.

I-II. Local Connection

Local connection is to directly connect the printer/MFP to a computer using a USB cable without the network.

Check that the USB cable is connected normally.

Note: If a message indicating that new hardware is added appears on the computer screen when connecting a USB cable, select **Cancel**.


In Windows 7 environment, double-click the icon that indicates the installation of the driver software in the notification area on the taskbar to open the application. Click “Skip obtaining driver software from Windows Update”, then skip the step to acquire driver software.

II. Installing Drivers

II-I. Network Connection

1. Install the printer driver.

On the main menu of the CD, click [Printer Driver] - [Install].



* The main menu of the CD is a reference example. The menu configuration may differ from this example on your software.


2. The [Installer License Agreement] window appears. Check the contents, then click [I Agree].
3. Follow the on-screen instructions to install the printer driver.
4. Install Network Twain Scan Driver.

On the main menu of the CD, click [Network Twain Scan Driver] - [Install].

5. Installing Network Twain Scan Driver starts, and completes automatically.
6. Install the fax driver.

On the main menu of the CD, click [FAX and Local TWAIN, WIA Scan Driver] - [Install].

7. The printer connection configuration window appears. Referring to the IP address for connecting the printer/MFP and the device name, select the desired port from Discovered Ports, then click [Continue]. Installing the driver starts.




8. When the installation completion window appears, click [Done] to complete installation processing.

II-II. Local Connection

1. Install the printer driver.

On the main menu of the CD, click [Printer Driver] - [Install].




- * The main menu of the CD is a reference example. The menu configuration may differ from this example on your software.
2. The [Installer License Agreement] window appears. Check the contents, then click [I Agree].
 3. Follow the on-screen instructions to install the printer driver.

4. Install the fax driver and Local TWAIN, WIA Scan Driver.

On the main menu of the CD, click [FAX and Local TWAIN, WIA Scan Driver] - [Install].

5. The printer connection configuration window appears. Referring to the printer/MFP name, select the desired USB port from Discovered Ports, then click [Continue].
Installing the driver starts.



- * For USB connection, Discovered Ports shows USB in Type, and USB001, USB002, USB003, and other names in Port Name.
6. When the installation completion window appears, disconnect and connect the USB cable from and to your computer. Installing Local TWAIN, WIA Scan Driver is completed by Plug and Play.
 - * In Windows XP environment, select "Install the software automatically" on the search wizard of new hardware, then click "Next" to complete installation processing.
 7. When the installation completion window appears, click [Done] to complete installation processing.
-